

Beekman Velvet

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	18.1 oz per linear yard
WIDTH	54"
COMPOSITION	100% Polyester
<input checked="" type="checkbox"/> PIECE DYED	<input type="checkbox"/> YARN DYED
<input type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD
	<input type="checkbox"/> FIBER DYED
	<input checked="" type="checkbox"/> PILE
YARN PER INCH	9.4 EPI, 8.6 PPI
YARN SIZE	300D Warp, 300D Fill
BACKING	None
STAIN RESISTANCE	PFAS Free
CLEANING CODE	S, Spot clean using water free solvent or dry cleaning product. Cleaning by a professional service is recommended.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000 Double Rubs*	ASTM D4157-13
BREAKING STRENGTH	308 Warp, 259 Fill	ASTM D5034-09
BRUSH PILL	Class 5	ASTM D3511
PILE RETENTION	Class 5	ASTM D4685-15
CROCKING RESISTANCE	5 Dry, 4.5 Wet	AATCC 8-2013
COLORFASTNESS TO LIGHT	Class 4.5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	77.4 Warp, 71.4 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	40.1 Warp, 40.2 Fill	ASTM D2261-13

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



DISTRIBUTED BY

EVOKE+

169 OCEAN ST., STE 200
 SOUTH PORTLAND, ME 04106

INFO@EVOKEPLUS.COM
 207.772.2703



*ACT® Registered Certification Marks