

Blarney

FABRIC & UPHOLSTERY SPECIFICATIONS

Content:	100% Polyurethane
Backing:	70% Polyester, 30% Cotton
Finish:	Wipe-Off - a high-performance stain and moisture repellent, based on Nanotechnology Antimicrobial
Weight:	20.3 oz per linear yard
Width:	54"
Abrasion:	Heavy Duty - Exceeds 200,000 Cycles (Wire Screen Abradant) (ASTM D415-07)
Light Fastness:	Class 4/200 hrs. min. (AATCC16A)
Color Fastness:	Class 4 (ASTM D3597, AATCC8) Wet Class 4 (ASTM D3597, AATCC8) Dry
Physical Properties:	Class 4 (ASTM D3511) Brush Pill 98 lb warp, 83 lb weft (ASTM D5034) Breaking Strength 84 lb warp, 85 lb weft (ASTM D4034) Seam Slippage 50,000 cycles (CFFA 10) Flex Resistance Pass (CFFA 6a) Cold Crack Pass (ISO 1419) 5 weeks
Passes:	California Tech. Bulletin #117 - 2013 UFAC Class 1 NFPA 260 Class 1 MVSS 302 Pass
Cleanability:	WS - Both water- and solvent-based solutions Bleach cleanable - 5:1 water/bleach solution
WARRANTY:	One Year