

## Constance

### GENERAL SPECIFICATIONS

Overall Composition	88% Polyester / 10% Polyurethane / 2% Silicone		
Backing Composition	Polyurethane		
Stain Repellent	Silicone Based, PFAS-free		
Weight	15.4 oz. Per Linear Yard		
	340 gsm		
Width	54"		
Direction	Non-Directional		
Weave Construction	<input checked="" type="checkbox"/> Dobby	<input type="checkbox"/> Jacquard	<input type="checkbox"/> Pile
Dyeing Type	<input type="checkbox"/> Piece Dyed	<input type="checkbox"/> Yarn Dyed	<input checked="" type="checkbox"/> Fiber Dyed
Fiber Composition (Synthetic/Natural)	100% Synthetic Fiber		
Fiber Type (Filament/Spun/Staple)	100% Filament		
High Tenacity Yarn	No		
Textured Yarn	Yes		
Yarns Per Inch	Warp: 25.4 EPI / Fill: 23.6 PPI		
Yarns Per Centimeter	Warp: 10 / Fill: 9.3		
Yarn Size	Warp: 1250D / Fill: 1250D		
Yarns Twisted 472 Turns+/Meter	No		

### PERFORMANCE SPECIFICATIONS

Abrasion Resistance	100,000+ Double Rubs*	ASTM D4157-13(2017)
Stain Resistance	Yes, PFAS-free	
Bleach Resistance	Yes, 10% Dilution	
Breaking Strength	Warp: 215 / Fill: 170	ASTM D5034-09(2017)
Brush Pill	Class 5.0	ASTM D3511
Colorfastness to Light	Class 5.0 / 40 Hours	AATCC 16.3-2014, Opt. 3
Crocking Resistance	Dry: 5.0 / Wet: 5.0	AATCC 8-2016
Seam Slippage	Warp: 87.5 / Fill: 93.0	ASTM D4034-92
Tear Strength: Tongue Tear	Warp: 27.3 / Fill: 24.0	ASTM D2261-13(2017)
Water Repellency Spray Test	100	AATCC 22-2014
Water Resistance Hydrostatic Pressure	270+ cm (maximum)	AATCC 127-2013, Opt. 1



\*ACT® Registered Certification Marks

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan

### FLAMMABILITY SPECIFICATIONS

California TB 117:13	Pass
UFAC Class I	Pass
NFPA 260	Pass

# Constance

## GENERAL PRODUCT INFORMATION

Country of Origin	China
HTS Code	5407.52.2060
Roll Size	45 Yards/Roll

## CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

## SPECIAL HANDLING

Some types of adhesive tape may delaminate the backing off of Supreen fabric. It is recommended to use self-clinging stretch wrap instead of tape to secure the roll.

## REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer. Practice Greenhealth does not verify this information.

**DISTRIBUTED BY**

**EVOKE+**

**169 OCEAN ST., STE 200  
SOUTH PORTLAND, ME 04106**

**INFO@EVOKEPLUS.COM  
207.772.2703**