

# Foundation

## GENERAL SPECIFICATIONS

Overall Composition	80% PVC / 20% Polyester
Surface Composition	100% PVC (Phthalate Free)
Backing Composition	100% Polyester
Weight	30.0 oz. Per Linear Yard
	663.2 gsm
Width	54"
Thickness	1.00 mm
Direction	Non-Directional

## PERFORMANCE SPECIFICATIONS

Abrasion Resistance	100,000+ Double Rubs*	ASTM D4157-13
Stain Resistance	Yes, PFAS-free	
Bleach Resistance	Yes, 10% Dilution	
Breaking Strength	Warp: 101 / Fill: 93	ASTM D751-06(2011)
Coating Adhesion	Warp: 10.27 / Fill: 11.50	ASTM D751-06(2011)
Cold Crack	-20° F	CFFA-6a-2010
Colorfastness to Light	Class 5.0 / 300 Hours	AATCC 16.3-2014, Opt. 3
Crocking Resistance	Dry: 5.0 / Wet: 5.0	AATCC 8-2013
Flex Resistance	25,000+	ASTM D2907-03
Sulfide Stain Resistance	Yes	
Seam Strength: Tack Tear	Warp: 50 / Fill: 50	ASTM D751-06(2011)
Tear Strength: Tongue Tear	Warp: 6.8 / Fill: 8.0	ASTM D2261-13
Stretch and Set	Warp: Stretch 25.04% / Set 2.59%	SAE J855-2009
	Fill: Stretch 36.45% / Set 3.80%	
	Bias: Stretch 33.22% / Set 2.94%	



\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## FLAMMABILITY SPECIFICATIONS

California TB 117:13	Pass
UFAC Class I	Pass
NFPA 260	Pass
FMVSS 302	Pass

## GENERAL PRODUCT INFORMATION

Country of Origin	China
HTS Code	5903.10.2090
Roll Size	30 Yards/Roll

# Foundation

## CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

## REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

Phthalate free / PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



## DISTRIBUTED BY

**EVOKE+**

169 OCEAN ST., STE 200  
SOUTH PORTLAND, ME 04106

INFO@EVOKEPLUS.COM  
207.772.2703