



FABRIC SPECIFICATIONS

PIP COLLECTION

Gigha

Content:	53% Polyester, 42% Polyurethane, 5% Silicone
Backing:	Polyester
Finish:	None
Weight:	23.5 oz. per linear yard
Width:	54"
Abrasion:	Heavy Duty – Exceeds 195,000 Cycles (Wyzenbeek – Cotton Duck Abradant) (ASTM D4157)
Light Fastness:	Class 4/200 hrs. min. (AATCC16A)
Color Fastness:	Class 4 (ASTM D3597, AATCC8) Wet Class 4 (ASTM D3597, AATCC8) Dry
Physical Properties:	50,000 cycles (CFFA 10) Flex Resistance 101 lbs. warp, 175 lbs. weft (ASTM D5034) Breaking Strength 70 lbs. warp, 44 lbs. weft (ASTM D4034) Seam Slippage
Passes:	California Tech. Bulletin #117 – 2013 UFAC Class 1 NFPA 260 Class 1
Cleanability:	Code - W/S Bleach Cleanable - 5:1 water/bleach solutions
WARRANTY:	3 Years
Origin:	China

The featured product prioritizes safety and environmental standards. It is free from chemicals listed in Prop 65, compliant with AB2998 regulations by excluding flame-retardant and anti-bacterial chemicals. Notably, it is 7P phthalate-free, lead, heavy metal, BPA, Tris, and formaldehyde-free, ensuring purity and safety.

WWW.EVOKEPLUS.COM