

Huxley

GENERAL SPECIFICATIONS

| | |
|---------------------|--|
| Overall Composition | 45% Polyurethane (Polycarbonate) / 55% Polyester |
| Surface Composition | 100% Polyurethane (Polycarbonate) |
| Backing Composition | 100% Polyester |
| Weight | 20.0 oz. Per Linear Yard |
| | 442.1 gsm |
| Width | 54" |
| Thickness | 1.00 mm |
| Direction | Non-Directional |

PERFORMANCE SPECIFICATIONS

| | | |
|-------------------------------|-----------------------------------|-----------------------------|
| Abrasion Resistance | 300,000+ Double Rubs* | ASTM D4157-13 |
| Stain Resistance | Yes, PFAS-free | |
| Hydrolysis Resistance | 7 Weeks | ISO 1419:1995 (Jungle Test) |
| Anti-Bacterial | Pass | AATCC 147-2011 |
| Bleach Resistance | Yes, 10% Dilution | |
| Blocking | Rating 1 | CFFA-4(2010) |
| Breaking Strength | Warp: 105 / Fill: 168 | ASTM D751-06(2011) |
| Coating Adhesion | Warp: Full Bond / Fill: Full Bond | ASTM D751-06(2011) |
| Cold Crack | -20° F | CFFA-6a-2010 |
| Colorfastness to Light | Class 4.5 / 200 Hours | AATCC 16.3-2014, Opt 3 |
| Crocking Resistance | Dry: 5.0 / Wet: 5.0 | AATCC 8-2013 |
| Denim Dye Transfer Resistance | Yes | Ford BN 112-09 |
| Flex Resistance | 25,000+ | ASTM D2097-03(2010) |
| Ink Resistance | Yes | |
| Mildew Resistance | Pass | ASTM G21-13 |
| Sulfide Stain Resistance | Yes | |
| Seam Strength: Tack Tear | Warp: 74.3 / Fill: 74.9 | ASTM D751-06(2011) |
| Tear Strength: Tongue Tear | Warp: 12.9 / Fill: 7.6 | ASTM D751-06(2011) |
| Stretch and Set | Warp: Stretch 8.97% / Set 0.69% | SAE J855-2009 |
| | Fill: Stretch 41.64% / Set 3.75% | |
| | Bias: Stretch 27.40% / Set 50.34% | |



*ACT® Registered Certification Marks

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAMMABILITY SPECIFICATIONS

| | |
|----------------------|------|
| California TB 117:13 | Pass |
| UFAC Class I | Pass |
| NFPA 260 | Pass |

Huxley

GENERAL PRODUCT INFORMATION

| | |
|-------------------|---------------|
| Country of Origin | Vietnam |
| HTS Code | 5903.20.2500 |
| Roll Size | 30 Yards/Roll |

CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer. Practice Greenhealth does not verify this information.

DISTRIBUTED BY

EVOKE+

**169 OCEAN ST., STE 200
SOUTH PORTLAND, ME 04106**

**INFO@EVOKEPLUS.COM
207.772.2703**