

EVOKE +

Limerick FABRIC SPECIFICATIONS

Content:	100% Vinyl
Backing:	100% Polyester
Finish:	Wipe-Off - a high-performance stain and moisture repellent, based on Nanotechnology, Antimicrobial
Weight:	40.19 oz per linear yard
Width:	54"
Abrasion:	Heavy Duty - Exceeds 100,000 Cycles (Wyzenbeek - Wire Screen Abradant) (ASTM D4157)
Light Fastness:	Class 4/200 hrs. min. (AATCC16A)
Color Fastness:	Class 5 min. (ASTM D3597, AATCC8) Wet Class 5 min. (ASTM D3597, AATCC8) Dry
Physical Properties:	Class 5 (ASTM D3511) Brush Pill 137 lb warp, 143 lb weft (ASTM D5034) Breaking Strength 88 lb warp, 94 lb weft (ASTM D4034) Seam Slippage 50,000 cycles (CFFA 10) Flex Resistance Pass (CFFA 6a) Cold Crack
Passes:	California Tech. Bulletin #117 - 2013 UFAC Class 1 NFPA 260 Class 1 MVSS 302 Pass
Cleanability:	1.) Soap & Water, 2.) Fantastic/409, 3.) 5:1 Water/Bleach Solution
WARRANTY:	One Year