

Moselle

GENERAL SPECIFICATIONS

| | | | |
|---------------------------------------|--|------------------------------------|-------------------------------------|
| Overall Composition | 94% Polyester / 4% TPU / 2% Silicone | | |
| Backing Composition | TPU | | |
| Stain Repellent | Silicone Based, PFAS-free | | |
| Weight | 23.5 oz. Per Linear Yard | | |
| | 520 gsm | | |
| Width | 54" | | |
| Direction | Non-Directional | | |
| Weave Construction | <input checked="" type="checkbox"/> Dobby | <input type="checkbox"/> Jacquard | <input type="checkbox"/> Pile |
| Dyeing Type | <input checked="" type="checkbox"/> Piece Dyed | <input type="checkbox"/> Yarn Dyed | <input type="checkbox"/> Fiber Dyed |
| Fiber Composition (Synthetic/Natural) | 100% Synthetic Fiber | | |
| Fiber Type (Filament/Spun/Staple) | 100% Filament | | |
| Staple Yarns Combed or Carded | Carded | | |
| High Tenacity Yarn | No | | |
| Textured Yarn | Yes | | |
| Yarns Per Inch | Warp: 26.2 EPI / Fill: 20.8 PPI | | |
| Yarns Per Centimeter | Warp: 10.3 / Fill: 8.2 | | |
| Yarn Size | Warp: T900D / Fill: T2.6N | | |
| Yarns Twisted 472 Turns+/Meter | Yes | | |

PERFORMANCE SPECIFICATIONS

| | | |
|---------------------------------------|-------------------------|---------------------------|
| Abrasion Resistance | 100,000+ Double Rubs* | ASTM D4157-13(2022) |
| Stain Resistance | Yes, PFAS-free | |
| Bleach Resistance | Yes, 10% Dilution | |
| Breaking Strength | Warp: 352 / Fill: 276 | ASTM D5034-21 |
| Brush Pill | Class 5.0 | ASTM D3511 |
| Colorfastness to Light | Class 5.0 / 40 Hours | AATCC 16.3, Opt. 3 - 2020 |
| Crocking Resistance | Dry: 5.0 / Wet: 5.0 | AATCC 8-2016 |
| Seam Slippage | Warp: 141 / Fill: 134 | ASTM D4034-92 |
| Tear Strength: Tongue Tear | Warp: 51.8 / Fill: 41.8 | ASTM D2261-13(2017) |
| Water Repellency Spray Test | 100 | AATCC 22-2014 |
| Water Resistance Hydrostatic Pressure | 270+ cm (maximum) | AATCC 127-2013, Opt, 1 |



*ACT® Registered Certification Marks

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan

FLAMMABILITY SPECIFICATIONS

| | |
|----------------------|------|
| California TB 117:13 | Pass |
| UFAC Class I | Pass |
| NFPA 260 | Pass |

Moselle

GENERAL PRODUCT INFORMATION

| | |
|-------------------|---------------|
| Country of Origin | China |
| HTS Code | 5407.52.2060 |
| Roll Size | 45 Yards/Roll |

CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

SPECIAL HANDLING

Some types of adhesive tape may delaminate the backing off of Supreen fabric. It is recommended to use self-clinging stretch wrap instead of tape to secure the roll.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer. Practice Greenhealth does not verify this information.

DISTRIBUTED BY

EVOKE+

**169 OCEAN ST., STE 200
SOUTH PORTLAND, ME 04106**

**INFO@EVOKEPLUS.COM
207.772.2703**