



Seaquest

GENERAL SPECIFICATIONS

Overall Composition	84% PVC / 16% Polyester
Surface Composition	100% PVC (Phthalate Free)
Backing Composition	100% Polyester
Weight	3 oz. Per Linear Yard 7 gsm
Width	54"
Thickness	1.02 mm
Direction	Non-Directional

PERFORMANCE SPECIFICATIONS

Abrasion Resistance	175,000+ Double Rubs*	ASTM D4157-07
Stain Resistance	Yes, PFAS-free	
Bleach Resistance	Yes, 10% Dilution	
Breaking Strength	Warp: 89.2 / Fill: 102.7	FTM 5100
Cold Crack	-20° F	CFFA-6a-2007
Colorfastness to Light	1,000 Hours	AATCC 16.3-2014, Opt. 3
UV Resistance	1,000 Hours	ASTM G154-12a
Flex Resistance	25,000+	ASTM D2907-03
Mildew Resistance	Pass	ASTM G21/CFFA 120
Pink Stain Resistance	Pass	ASTM E1428
Sulfide Stain Resistance	Yes	



*ACT® Registered Certification Marks

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAMMABILITY SPECIFICATIONS

California TB 117:13	Pass
UFAC Class I	Pass
NFPA 260	Pass
FMVSS 302	Pass

GENERAL PRODUCT INFORMATION

Country of Origin	China
HTS Code	5903.10.2090
Roll Size	30 Yards/Roll

Seaquest

CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

Phthalate free / PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



DISTRIBUTED BY

EVOKE+

**169 OCEAN ST., STE 200
SOUTH PORTLAND, ME 04106**

**INFO@EVOKEPLUS.COM
207.772.2703**